





Speaker Overview


July 1, 2009


Surface Mounted Speakers			
<p>SQUARE 8" Speaker External Dimension: 11.7" x 11.7" Depth: 4.00" Sensitivity (1w/1m) : 92 db SPL White Epoxy Wall or Ceiling Mount</p>			
IP-Enabled		Analog	
Standard	SPKR-IP System 1	Standard	SPKR-1-T
Vandal-Proof	SPKR-IP System 1VP	Vandal-Proof	SPKR-VP-T
<p>SLANTED 8" Speaker External Dimension: 11.4" x 11.7" Depth: 5.4" to 3.0" Sensitivity (1w/1m) : 92 db SPL White Epoxy Wall Mount</p>			
IP-Enabled		Analog	
Standard	SPKR-IP System 2	Standard	SPKR-3-T
Vandal-Proof	SPKR-IP System 2VP	Vandal-Proof	SPKR-2VP-T
IP-Enabled Bi-Directional Hallway Speaker			
<p>Rectangular Dual, 4" Speakers External Dimension: 7.25" x 4.5" x 4.5" Depth: 5.5" Sensitivity (1w/1m) : 93 db SPL White Epoxy Wall Mount</p>			
IP-Enabled			
Standard	SPKR-11-BD-P		


Speaker Overview


July 1, 2009

Acoustical Tile Lay-in Speaker		
<p>SQUARE</p> <p>8" Speaker</p> <p>External Dimension: 23.75" x 23.75" Depth: 3.4"</p> <p>Sensitivity (1w/1m) : 92 db SPL</p> <p>White Epoxy</p>		
Analog		
Standard		SPKR-12-T

Beam Mounted Speaker		
<p>Round</p> <p>8" Speaker</p> <p>External Dimension: 12.9" Depth: 4.1"</p> <p>Sensitivity (1w/1m) : 95 db SPL</p> <p>White Epoxy</p>		
Analog		
Standard		SPKR-BB2-T

Surface Mounted Outdoor Speaker		
<p>SQUARE</p> <p>4" High-Performance Speaker</p> <p>External Dimension: 5.1" x 5.1" Depth: 2.4"</p> <p>Sensitivity (1w/1m) : 91 db SPL</p> <p>Black Epoxy</p>		
Analog		
Weather-Proof		SPKR-7DT-T

Surface Mounted Horn		
<p>SQUARE</p> <p>8" Re-Entrant Horn</p> <p>External Dimension: 11.7 x 11.7" Depth: 4.00"</p> <p>Sensitivity (1w/1m) : 110 db SPL</p> <p>White Epoxy</p>		
Analog		
Vandal-Proof		SPKR-6HVP-T

Weather Resistant Horn		
<p>Bell Shaped</p> <p>8" Horn</p> <p>External Dimension: 9.2" x 8.9"</p> <p>Sensitivity (1w/1m) : 110 db SPL</p> <p>Tan Enamel Wall or Pole Mount</p>		
Analog		
Vandal-Proof		SPKR-6H16-T

Large Area External Horn		
<p>SQUARE</p> <p>400 Watt, 8 Ohm Horn</p> <p>External Dimension: 19.0", Radius Depth: 21.0"</p> <p>Sensitivity (1w/1m) : 111 db SPL</p> <p>Standard Wall or <i>Optional</i> Pole Mount</p>	<p><i>Image</i></p> <p><i>Unavailable</i></p>	
Tan Enamel		
Analog		
Standard		SPKR-H-400